

US Patent 5,611,049, Claim 1:

1. In a network of digital computers that includes a first plurality of Network Distributed Cache ("NDC") sites, each NDC site including an NDC that has an NDC buffer, a method for projecting images of a stored dataset from an NDC server terminator site into a second plurality of NDC client terminator sites in response to requests to concurrently access such stored dataset transmitted from a third plurality of client sites respectively to the second plurality of NDC client terminator sites, the method comprising the steps of:
- | |
|---|
| (a) the NDC receiving the request to access data in the stored dataset; |
| (b) the NDC checking the NDC buffer at this NDC site to determine if a projected image of data requested from the stored dataset is already present there; |
| (c) if the NDC buffer of this NDC site does not contain a projected image of all data requested from the stored dataset, and if the NDC site receiving the request is not the NDC server terminator site for the stored dataset, the NDC of this NDC site transmitting a request for data from this NDC site downstream to another NDC site closer to the NDC server terminator site for the stored dataset than the present NDC site; |
| (d) if the NDC buffer of this NDC site does not contain a projected image of all data requested from the stored dataset, and if the NDC site receiving the request is the NDC server terminator site for the stored dataset, the NDC of the NDC server terminator site accessing the stored dataset to project an image of the requested data into the NDC buffer of the NDC server terminator site; |
| (e) repeating the steps (a) through (d) until the NDC buffer of the downstream NDC site receiving the request contains a projected image of all requested data; |
| (f) each successive NDC site, having obtained a projected image of all the requested data, returning the requested data upstream to the NDC site from which the NDC site received the request until the requested data arrives at the NDC client terminator site, each NDC site that returns data upstream to the requesting NDC site retaining a copy of the returned data that the returning NDC site may subsequently transmit to an NDC site other than the NDC site to which the returning NDC site first returned the data, whereby images of the stored dataset may be projected concurrently from a single NDC site into the second plurality of NDC client terminator sites; and |
| (g) the NDC client terminator site, upon receiving the requested data, returning the requested data to the client site that requested access to the stored dataset. |

Novell				Total Only			
WHAT'S NEW	HOW TO BUY	SEARCH	SITE MAP				
PRODUCT INFO	PRODUCT RESOURCES	COMPETITIVE INFO	PRI 33	NEWS			
RELATED PRODUCTS	EVAL FW	SUPPORT	BMSB HOME				

SEPTEMBER 1997

NOVELL MESSAGES

Three Ways to Deliver Cached Performance to Your Intranet and Internet Users

RON LEE
Senior Research Engineer
Advanced Development Group

Network engineers and administrators are constantly trying to squeeze the highest performance out of their systems using the most cost-effective means available. Yet the widespread deployment of Internet and intranet connections has imposed new requirements that seem to be in conflict with these efforts to enhance network performance. Comprehensive security restrictions, access controls, and content filtering are crucial aspects of securing the intranet and connecting to the Internet, but they exact an additional performance penalty in an environment where users are already frustrated by busy Web servers and long response times.

Novell's BorderManager includes an Internet object cache that significantly increases the speed of web access. In the process, this technology provides a performance foundation to support your network infrastructure and offset the performance penalty you pay for the necessary security controls and filtering.

This AppNote provides an overview of BorderManager's caching technology and discusses the advantages of caching in Intranet and Internet environments. It then describes three applications of Novell's Internet object cache that provide significant benefits to internet and Internet users:

- ==== Proxy caching
- ==== Proxy cache hierarchies
- ==== Web server acceleration

For more information on BorderManager and other AppNotes regarding these technologies, visit the Novell World Wide site at <http://www.novell.com/bordermanager/>.

What is Caching?

During the 1960s, computer designers discovered that much of the program code their systems were executing was extremely repetitive—small portions of the code would be processed over and over again. Using this insight to their advantage, they began storing the repetitive portions of their programs in a

<http://www.novell.com/bordermanager/cache.html> [1 of 1] [02/24/1998 4:53:26 PM]




Figure 8




Figure 6




Figure 5

- (a) **the NDC receiving the request** to access data in the stored dataset;
- (b) **the NDC checking the NDC buffer** at this NDC site to determine if **a projected image of data requested** from the stored dataset is already present there;
- (c) **if the NDC buffer of this NDC site does not contain a projected image of all data requested** from the stored dataset, and if the NDC site receiving the request **is not the NDC server terminator site** for the stored dataset, **the NDC of this NDC site transmitting a request for data** from this NDC site **downstream to another NDC site** closer to the **NDC server terminator site** for the stored dataset than the present NDC site;
- (d) **if the NDC buffer of this NDC site does not contain a projected image of all data requested** from the stored dataset, and if the NDC site receiving the request **is the NDC server terminator site** for the stored dataset, **the NDC of the NDC server terminator site accessing the stored dataset to project an image of the requested data** into the NDC buffer of the NDC server terminator site;
- (e) **repeating the steps (a) through (d)** until the NDC buffer of the downstream NDC site receiving the request contains **a projected image of all requested data**;





Figure 8



~~Figure 6~~




Figure 5

- (a) **the NDC receiving the request** to access data in the stored dataset;
- (b) **the NDC checking the NDC buffer** at this NDC site to determine if a **projected image of data requested** from the stored dataset is already present there;
- (c) **if the NDC buffer of this NDC site does not contain a projected image of all data requested** from the stored dataset, and if the NDC site receiving the request **is not the NDC server terminator site** for the stored dataset, **the NDC of this NDC site transmitting a request for data** from this NDC site **downstream to another NDC site** closer to the **NDC server terminator site** for the stored dataset than the present NDC site;
- (d) **if the NDC buffer of this NDC site does not contain a projected image of all data requested** from the stored dataset, and if the NDC site receiving the request **is the NDC server terminator site** for the stored dataset, **the NDC of the NDC server terminator site accessing the stored dataset to project an image of the requested data** into the NDC buffer of the NDC server terminator site;
- (e) **repeating the steps (a) through (d)** until the **NDC buffer of the downstream NDC site receiving the request** contains a **projected image** of all requested data;